



The Hallmark of Oil Maintenance

FOCUS PORTABLE UNITS

For Electric Portable Oil Reclamation

Filtroil's portable filtration carts can be easily transported through plant environments handling tough reclamation jobs to fine oil polishing requirements with self contained pump motor. The multiple housings allow for higher dirt and water holding capacities while the control panel monitors all necessary unit functions.

FOCUS-400



FOCUS-800



FOCUS-1200



SUITED FOR:


compressor gear
hydraulic insulating
lubrication machine,
rolling spindle trans
turbine washing oils



APPLICATION:

off-line,
on-line,
new oil,
transfer,
reclamation, and
bulk tanks

SPECIFICATIONS FOR FOCUS PORTABLE UNITS



total dirt-holding capacity	2.5 lbs.	5 lbs.	7.5 lbs.
total water removing capacity	Up to 48 ozs.	Up to 96 ozs.	Up to 144 ozs.
description	(2) BU-200 canisters for utilizing the Filtroil 200E and 200ME (water-removal) elements. Filtering accuracy down to 0.1 micron achieving ISO codes of 16/14/11 or better	(4) BU-200 canisters for utilizing the Filtroil 200E and 200ME (water-removal) elements. Filtering accuracy down to 0.1 micron achieving ISO codes of 16/14/11 or better	(6) BU-200 canisters for utilizing the Filtroil 200E and 200ME (water-removal) elements. Filtering accuracy down to 0.1 micron achieving ISO codes of 16/14/11 or better
size	30.32" (L) X 14.17" (W) X 22.44" (H)	30.3" (L) X 22.4" (W) X 19.7" (H)	41.0" (L) X 22.4" (W) X 19.7" (H)
weight	165 lbs.	310 lbs.	350 lbs.
flow rate	2.1 GPM	4.2 GPM	5.8 GPM
power supply	110 V / 220 V / 380V, 50 or 60 Hz	110 V / 220 V / 380V, 50 or 60 Hz	110 V / 220 V / 380V, 50 or 60 Hz
control panel	Pressure Gauge, Vacuum Gauge, Operating Lamp, On/Off Button	Time Controller, Temperature Gauge, Pressure Gauge, Vacuum Gauge, Operating Lamp, On/Off Button	Time Controller, Temperature Gauge, Pressure Gauge, Vacuum Gauge, Operating Lamp, On/Off Button
portability	Caster wheels and quick disconnects allow excellent mobility	Caster wheels and quick disconnects allow excellent mobility	Caster wheels and quick disconnects allow excellent mobility
in-line filter	Pump protected by 80 µm suction filter	Pump protected by 80 µm suction filter	Pump protected by 80 µm suction filter



For more information, contact: 2256 Dabney Road, Suite G
Richmond, VA 23230
Toll Free: 800-638-3866
804-359-9125 Fax: 804-359-9128
filtroil@filtroil.com