



BLACK GOLD Handheld

Designed to clean, purify, and dry-out insulating and lubricating oil with the simplicity of a handheld and spin on filters.



Specifications

- Can see viscosities from 10 cSt to 460 cSt.
- Plumbed with all steel fittings.
- 1/3 HP Viking motor 50/60 MHz with MTO.
- 4 GPM mechanically sealed positive displacement pump.
- Wired 115/230 volt, 6.0/3.0 amps.
- 60 PSI pressure gauge.
- 10 micron Beta 1000 spin on filter.
- Water removal filter, 170 ml water holding capacity.
- Pelican 1640 Case - water tight, crush proof, and dust proof construction.

Industry Applications

Can Filter:

- Drums
- Process Pumps
- Totes
- Load Tap Changer top-offs
- Gear Boxes
- Power Units

PELICAN 1640 Case Contents

- (1) FMX-HDSP filtration system.

Female Adaptors.

1. 1" NPT x 3/4" camlock.
2. 3/4" NPT x 3/4" camlock.
3. 1/2" NPT x 3/4" camlock.

Male Adaptors.

1. 1" NPT x 3/4" camlock.
 2. 3/4" NPT x 3/4" camlock.
 3. 1/2" NPT x 3/4" camlock.
- (2) 10 micron BETA 1000 Particulate filter.
 - (1) 170 ml water removal filter.
 - 3/4" PTFE tape.
 - Gaskets and hitch pins.
 - Replacement female and male camlock fittings.
 - (2) 10ft 3/4" hydraulic hoses with fitted ends.
 - (Optional) Push button oil sample port.



Filtroil, LLC - Headquarters
2600 E. Cary Street, Suite 5102
Richmond, Virginia 23223

TEL: 800.638.3866
TEL: 804.359.9125
EMAIL: filtroil@filtroil.com